

R 723.850	C 220	H 46
R 723.851	C 220	H 59
R 723.852	C 350	H 65
R 723.853	C 350	H 82



R 723.856	C 220	H 60
R 723.857	C 330	H 82




R 723.860	C 145	H 33
------------------	-------	------



R 723.861	C 180	H 62
------------------	-------	------



R 723.862	C 50	H 100
------------------	------	-------



L 61 H 48

R 723.863Ruota superiore
di guida in Ottone

R 723.870	D 30	H 26	F M8
R 723.871	D 37	H 30	F M10

Ruota superiore
di guida in Nylon

R 723.873	D 34	H 30	F M10
R 723.874	D 38	H 30	F M10
R 723.875	D 34	H 30	F M10

Perno, rondelle e dadi zincati




R 723.877	D 60	H 60
------------------	------	------

Nylon: R723.880 → R723.883
Ottone: R723.884 → R723.887

R 723.880	D 25	H 32	F M14
R 723.881	D 40	H 44	F M16
R 723.882	D 30	H 40	F M14
R 723.883	D 40	H 60	F M16
R 723.884	D 25	H 32	F M14
R 723.885	D 40	H 44	F M16
R 723.886	D 30	H 40	F M14
R 723.887	D 40	H 60	F M16



R 723.897	D=192 B=50
R 723.898	D=115 B=70




L 90 H 98

R 723.900

L 110 H 104

R 723.901


L 110 H 262,5

R 723.902

D 192 B50

R 723.897

D 115 B70

R 723.898**R723.914** C =25/35**R 723.915** C =25/42**R 723.916** C =25/52


C 42 A 59

R 723.904

C 52 A 69

R 723.905

C 62 A 79

R 723.906


C 25 A 35

R 723.910

C 25 A 42

R 723.911

C 25 A 52

R 723.912

C 42 A 216

R 723.957

C 52 A 216

R 723.958

C 62 A 216

R 723.959


C 42 A 216

R 723.965

C 52 A 216

R 723.966

C 62 A 216

R 723.967

B 210 L 25

R 723.950

B 118 L 21,5

R 723.951**R723.970** C =25/35**R 723.971** C =35/45**R 723.972** C =40/50**R 723.973** C =50/60**R 723.974** C =25/35**R 723.975** C =35/45**R 723.976** C =40/50**R 723.977** C =50/60A ALLUMINIO
ALUMINIUMC RAME
TAPEREDF PIATTO RIGATO
FLUTEDG ZINCATO
GALVANIZEDR RASTREMATO
TAPEREDEFFETTO MATTONE
HAMMER EFFECT