

2 ali - Perno sfilabile con rondella
2 wings - Take off hinge with washer



R 700.100	60 mm
R 700.101	80 mm
R 700.102	100 mm
R 700.103	120 mm
R 700.104	140 mm
R 700.105	170 mm
R 700.106	200 mm

3 ali - Perno sfilabile con rondella
3 wings - Take off hinge with washer



R 702.100	80 mm
R 702.101	100 mm
R 702.102	120 mm
R 702.103	140 mm
R 702.104	170 mm
R 702.105	200 mm

Cerniera a tappo con 2 ali
Hinge with plug and 2 wings




R 704.100	60 mm
R 704.101	80 mm
R 704.102	100 mm
R 704.103	120 mm
R 704.104	140 mm

Profilo a goccia - Perno in ferro ottonato con rondella fissa
Tear profile - Brass iron hinge with fixed washer



R 706.100	40 mm	D 6 mm
R 706.102	80 mm	D 7 mm
R 706.103	100 mm	D 8 mm
R 706.104	120 mm	D 9 mm
R 706.105	140 mm	D 9 mm
R 706.106	140 mm	D 10 mm
R 706.107	140 mm	D 12 mm
R 706.108	150 mm	D 14 mm



2 ali aperte. Perno sfilabile
1 rondella in ottone
2 opened wings. Take off hinge
1 brass washer



R 708.100	90 mm
R 708.101	180 mm

2 ali aperte. Perno sfilabile
1 cuscinetto
2 opened wings. Take off hinge
1 bearing



R 708.110	90 mm
R 708.111	180 mm

2 ali chiuse. Perno sfilabile
1 cuscinetto
2 closed wings. Take off hinge
1 bearing



R 710.100	90 mm
R 710.101	180 mm

Cerniere zincate
b/g lunghe
perno fisso mm. 26x140



R 706.270	180 mm
-----------	--------

DISPONIBILE
ANCHE
LA GAMMA IN
ACCIAIO INOX



3 ali chiuse. Perno sfilabile
2 cuscinetto
3 closed wings. Take off hinge
2 bearing

R 714.100	180 mm
-----------	--------